



The Enphase Energy Microinverter System improves energy harvest, increases reliability, and dramatically simplifies design, installation and management of solar power systems.

The Enphase System includes the microinverter, the Envoy Communications Gateway, and Enlighten, Enphase's monitoring and analysis software.

**PRODUCTIVE**

- Maximum energy production
- Resilient to dust, debris and shading
- Performance monitoring per module

**RELIABLE**

- System availability greater than 99.8%
- No single point of system failure

**SMART**

- Quick and simple design, installation and management
- 24/7 monitoring and analysis

**SAFE**

- Low voltage DC
- Reduced fire risk



# M215 — MICROINVERTER TECHNICAL DATA

Input Data (DC)		M215-60-2LL-S22/S23 and M215-60-2LL-S22-NA/S23-NA (Ontario)	
Recommended input power (STC)	190 - 260W		
Maximum input DC voltage	45V		
Peak power tracking voltage	22V - 36V		
Operating range	16V - 36V		
Min./Max. start voltage	22V/45V		
Max. DC short circuit current	15A		
Max. input current	10.5A		
Output Data (AC)		@208 Vac	@240 Vac
Maximum output power	215W	215W	
Nominal output current	1.0A (arms at nominal duration)	0.9A (arms at nominal duration)	
Nominal voltage/range	208V/183-229V	240V/211-264V	
Extended voltage/range	208V/179-232V	240V/206-269V	
Nominal frequency/range	60.0/59.3-60.5 Hz	60.0/59.3-60.5 Hz	
Extended frequency range	60.0/59.2-60.6 Hz	60.0/59.2-60.6 Hz	
Power Factor	>0.95	>0.95	
Maximum units per 20A branch circuit	25 (three phase)	17 (single phase)	
Maximum output fault current	1.05 Arms, over 3 cycles; 25.2 Apeak, 1.74ms duration		
Efficiency			
CEC weighted efficiency		96.0%	
Peak inverter efficiency		96.3%	
Static MPPT efficiency (weighted, reference EN50530)		99.6%	
Dynamic MPPT efficiency (fast irradiation changes, reference EN50530)		99.3%	
Night time power consumption		46mW	
Mechanical Data			
Ambient temperature range	-40°C to + 65°C		
Operating temperature range (internal)	-40°C to + 85°C		
Dimensions (WxHxD)	17.3 cm x 16.4 cm x 2.5 cm (6.8" x 6.45" x 1.0")*		
Weight	1.6 kg (3.5 lbs)		
Cooling	Natural convection - No fans		
Enclosure environmental rating	Outdoor - NEMA 6		
			* without mounting bracket
Features			
Compatibility	Pairs with most 60-cell PV modules		
Communication	Power line		
Warranty	25-year limited warranty		
Monitoring	Free lifetime monitoring via Enlighten software		
Compliance	UL1741/IEEE1547, FCC Part 15 Class B CAN/CSA-C22.2 NO. 0-M91, 0.4-04, and 107.1-01		

## Enphase Energy, Inc.

201 1st Street  
 Petaluma, CA 94952  
 Phone: 877-797-4743  
 Fax: 707-763-0784

[info@enphaseenergy.com](mailto:info@enphaseenergy.com)  
<http://www.enphase.com>

Available from:

